

Index

- A/D converter 311
- absorption rate 26, 163
- acceleration measurement 315
- access authorisation 385
- access control 385–8
- access protection page 298–300
- access register 293
- access rights 292
- acoustomagnetic security systems 38–9
- activation field 234–6
- activator 29
- active mode, NFC 57–9
- active transponders 13, 22–4, 76, 137
- address and security logic 286–9
- administration code 295
- advanced mode 237–8
- advanced transponders 236–40
- air gap 48
- air interface (Part 1) 236–8
- Ali Baba 226
- ALOHA procedure 199–201, *See also* Slotted ALOHA (S-ALOHA) procedure
- amorphous metal 35–6, 38, 110
- amplitude modulation 43, 52, 97, 99, 141, 181, 183
- amplitude shift keying (ASK) 182–4
- anharmonic 39
- animal identification 25, 233–40, 391–8
- animal identification, standardisation 233–40
 - full/half-duplex system 235–6
 - ISO/IEC 11784 (Code Structure) 233–4
 - ISO/IEC 11785 (Technical Concept) 234
 - ISO/IEC 14223 (advanced transponders) 236–40
- sequential system 236
- antennas 116–27, *See also* Dipole antennas
 - coil 331, 333
 - current 64, 81, 84, 219
 - dipole antennas 122–4, 177
 - effective aperture 119–22
 - effective length 122
 - EIRP 118
 - ERP 118
 - gain and directional effect 117–18
 - input impedance 118–19
 - patch or microstrip antenna 125–7
 - radiation resistance 118
 - radius 65
 - scatter aperture 119–22
 - slot antennas 127
 - Yagi–Uda antenna 124
- anticollision algorithms/procedures 24, 99, 194–211, 222, 327, 381
- ALOHA procedure 199–201
- broadcast 194
- frequency domain multiple access (FDMA) 197
- space division multiple access (SDMA) 196–7
- spread-spectrum 194
- time domain multiple access (TDMA) 197–9
- anti-theft systems for goods, standardisation (VDI 4470) 29, 267–70
- application code (MAD) 295
- application data contained therein (APDU) 226
- application directory 295–7
- application identifier 273
- application layer 273–4

- application software 317, 324, 341
- artificial interocular lens 418
- ASK modulation 142, 245, 288, 326
- asymmetrical key procedure 230
- attacks on RFID systems 214–26
 - attempted attack 226
 - deception 215
 - denial of service 215
 - protection of privacy 215
 - on RF interface 216–26, *See also* RF interface, attacks on
 - spying out 215
 - on transponder 215–16
- authentication 24, 27, 226, 228, 292, 400
- auto-ID systems 2–6, *See also* Barcode systems; Biometrics
 - different ID systems, comparison 7–8
 - Homepage 422
- automatic fare collection (AFC) 362, 366
- automatic identification procedures (Auto-ID) 1
- automotive industry 414

- backscatter systems 22, 48
 - coupling 219–22
 - modulated 139–41, 283
 - transponder 171
- baked enamel 351
- bandwidth 162
- barcode labels/systems 1–3, 272
 - Code 2/5 interleaved 3
 - Code 39 3
 - Code Codabar 3
 - EAN coding 3
- baseband, coding in 179–81
- basic access control (BAC) 383
- battery 137
- ending measurement 315
- benefits of RFID systems 413
- bidirectional serial interface (I/O port) 4
- binary search procedure 198, 209–11
 - tree algorithm 222, 248
- biometrics 4
 - fingerprinting procedures (Dactyloscopy) 4
 - voice identification 4
- Bit 6 207
- bit coding 204
- block structure 291
- blocker tag attacks 223
- bolus 394

- broadcast 194
- busy signal 383

- calibration coil tests, smart cards 263–4
- CALYPSO 368–72
- cancellation in microwave transponders 137–8
- capacitance diodes 33
- capacitive (electric) coupling 22, 49–50, 241
- capacitive modulation 97–8, 242
- capture effect 202
- car keys 13
- carrier circuit 179
- carrier oscillation 182
- carrier pigeon races, animal identification 395–8
- CE mark 172, 429
- chaining, single-chip reader IC 328
- Channel 166, 195
- characteristic wave impedance 112–14
- charging capacitor 52
- checksum procedure 189–93
 - cyclic redundancy check (CRC) procedure 191
 - longitudinal redundancy check (LRC) procedure 190–1
 - parity checking 189–90
- chip 6
- cipher/ciphering 229–30
- circuit damping 75
- circular polarisation 114, 126
- clamping device identification 267
- clocks 17–18
- close-coupling smart cards 241–3
 - answer to reset and transmission protocols (Part 4) 241, 243
 - applications 362
 - dimensions and location of coupling areas (Part 2) 241
 - electronic signals and reset procedures (Part 3) 241–2
 - physical characteristics (Part 1) 241
 - test methods for 263
- close coupling systems 21, 48–9
 - reader to transponder, data transfer 49–50
 - transponder to reader, data transfer 49
 - transponder, power supply to 48–9
- CNC technology 409
- coaxial cable 333
- Code 2/5 interleaved 3
- Code 39 3

- Code Codabar 3
- code division multiple access (CDMA) 194
- coding 179–88
 - in baseband 179–81
 - line codes 179
- coil-on-chip technology 20–1
- coil resistance 72
- collar transponder 392
- collision interval 202
- communication system 179
- components of RFID system 6–9
 - reader 6, 8
 - transponder 6, 8
- compression measurement 315
- conductor loop 84, 112
- conductor loop antenna 85
- configuration register 292
- connection technique 356–8
- contact smart card 303
- contacting 356
- contactless clock 17
- contactless interface unit (CIU) 305
- contactless payment systems 372–5
 - closed 372
 - ExpressPay by American Express® 374
 - MasterCard® 374
 - open 372
 - Visa® Contactless 374–5
- contactless smart cards 18–19, 22, 361–2
- contactless smart cards, manufacture of 352–9
 - coil manufacture 352–6
 - cut clamp technology (CCT) 357
 - lamination 359
 - reflow soldering procedure 357
- contactless smart cards, standardisation 240–67
 - ISO/IEC 10373 (test methods for smart cards) 263–7, *See also* Smart cards
 - ISO/IEC 10374 (container identification) 267
 - ISO/IEC 10536 (close-coupling smart cards) 241–3
 - ISO/IEC 14443 (proximity-coupling smart cards) 243–58, *See also* Proximity-coupling smart cards
 - ISO/IEC 15693 (vicinity-coupling smart cards) 258–63, *See also* Vicinity-coupling smart cards
 - ISO/IEC 69873 (data carriers for tools and clamping devices) 267
- contactless technology 1
- container identification (ISO/IEC 10374) 267, 403–5
- control unit, readers 323–4
- coprocessor 25
- country signing certification authority 382
- coupling
 - capacitive 22, 49
 - electric 22, 49
 - inductive 22, 61, 112, 162
 - magnetic 22
- coupling coefficient (k) 89–91
 - measuring 100–2
 - of RFID magnetic field 68–70
- coupling element 9, 241
- coupling feature of RFID 21–2
- coupling loss 320
- cryptographic co-processor 213, 305
- cryptological key 227
- cryptological procedures 24
- cryptological unit 286
- crystal lattice 146
- current matching 54
- cut clamp technology (CCT) 357
- cyclic redundancy check (CRC) procedure 189, 191–3, 236, 257, 305
- dactyloscopy 4
- data block 256
- data carrier 7
- data encryption standard (DES) 305
- data integrity 189–211, *See also* Anticollision; Checksum procedure
- data transfer 179
- data transmission 94
- DBP code 181
- deactivation devices, inspection guidelines for customers 270
- deactivation rate 270
- deactivator 31
- deception 215
- deciphering 229
- decryption, dual interface card 306
- demodulation 179, 181, 283, 286
- demodulator 179
- denial of service 215
- derived keys, authentication using 228
- detection rate 29, 267
- dice 348
- die 347
- dielectric gap 108

- differential bi-phase code 236
- differential code 179, 181
- differentiation features of RFID 11–28, *See also* Selection criteria for RFID; Transponder(s): construction formats
 - backscatter systems 22
 - coupling 21–2, *See also* Coupling feature of RFID
 - data capacities of transponders 11
 - data carrier's operating principle 12
 - data quantity 12
 - data storage 12
 - data transfer from transponder to reader 12
 - electronic article surveillance (EAS) 11
 - frequency 21–2
 - frequency range 12–13
 - full-duplex (FDX)/half-duplex (HDX) systems 11
 - fundamental 11–13
 - operation type 12
 - power supply 12–13
 - range 21–2
 - response frequency 12
 - sequence 12
 - sequential systems (SEQ) 11
 - state machines 12
 - surface acoustic wave transponders 22
 - transmission frequency 13
 - writable transponders 12
- digital modulation procedures 180–8
 - 2 frequency shift keying (2 FSK) 185
 - 2 phase shift keying (PSK) 185–6
 - amplitude modulation 181
 - amplitude shift keying (ASK) 182–4
 - carrier 181
 - duty factor 182
 - frequency modulation 181
 - load resistance 187
 - modulation procedures with subcarrier 187–8
 - multilevel modulation 187
 - phase modulation 181
 - subcarrier frequency 187
- digital signature 382
- dimples 31
- Diode, Schottky 47
- dipole antennas 55, 110, 117, 122–4
 - 2-wire folded dipole 122
 - half-wave dipole ($\lambda/2$ dipole) 122
 - shortening factor 123
- direction of maximum radiation 124
- directional antenna in radio technology 124
- directional beam 26
- directional coupler 48, 320
- directional coupling 320
- directivity 321
- director 124
- Discovery Services (DS) 275
- disk (coin) format 13–14
- disk transponder 14
- Dopant profile 33
- Doppler effect 312–13
- driver 325
- dual interface card, architecture 25, 303–7
 - asymmetric key algorithms 306
 - coprocessors 303
 - cryptographic algorithms 303
 - MIFARE® Plus 304–5
 - modern concepts for 305–7
 - PMU (power management unit) 304
 - security requirements 304
- dual port EEPROM 297–300
- duty factor 182
- dynamic binary search procedure 209–11
- dynamic S-ALOHA procedure 203–4

- EAN code 3
- EAN/UCC-128 274
- ear tag 392
- EAS 11 29, 173
- EAS system 24
- Eddy currents 71
 - losses 108
- EEPROM 414
 - lifetime 309
 - write time 310
- effective aperture, antennas 119–22
- effective height 122
- effective length, antennas 122
- EIRP 118
- electric coupling 22
- electric field 22, 110
- electric rotational field 70
- electrical coupling 50–2
 - passive transponders, power supply of 50
 - transponder to reader, data transfer 50–2
- electrical field 50
- electrically erasable programmable read-only memory (EEPROMs) 12
- electrode 50

- electromagnetic backscatter coupling 45–8
 - free space path loss 46
 - operating principle 48
 - transponder to reader, data transfer 47–8
 - transponder, power supply to 45–7
- electromagnetic field 21
- electromagnetic interference field 26
- electromagnetic procedure 35–8
- electromagnetic types, 1-bit transponders 35–8
- electromagnetic waves 110–44
 - characteristic wave impedance 112–14
 - field strength (E) 112–14
 - free space attenuation 112
 - generation 110–12
 - near-field to far-field transition in
 - conductor loops 112
 - polarisation of 114–16
 - radiation density (S) 112
 - reflection of 115–16
 - spherical emitter 112
- Electronic Article Surveillance (EAS) systems 11, 24, 168–70, 173
 - electromagnetic procedure 35
 - frequency divider procedure 34–5
 - microwave systems 33–4
 - RF procedure 29
- electronic data carriers, architecture 283–315,
See also Transponder(s): with memory function
 - physical variables, measuring 311–15
- electronic immobilisation 13, 398–403
 - authentication 400
 - functionality of 399–401
 - motor electronics 400
 - procedure 399–400
 - success story 401–2
- electronic passport 380–3
 - anticollision algorithm 381
 - basic access control (BAC) 383
 - country signing certification
 - authority 382
 - design of 380
 - digital signature 382
 - fingerprint 381
 - machine-readable zone (MRZ) 382–3
 - position of 380
 - serial number 381
- electronic product code (EPC) 275, 277–8
 - introduction 280–2
- embedding technique 352–3
- EN 300 220 170–1, 424
- EN 300 330 162, 170, 424
- EN 300 440 170–1, 424
- encryption 27
 - dual interface card 306
 - encrypted data transfer 228–32
- end-of-burst detector 54
- energy range 80, 219, 322
- EPC Information Services (EPCIS) 275
- EPCglobal Middleware 275
- EPCglobal Network 274–82
 - discovery services (DS) 275
 - electronic product code (EPC) 275, 277–8, 280–2
 - EPC information services (EPCIS) 275
 - EPCglobal Middleware 275
 - Generation 2 276
 - GIAI (global individual asset identifier) 279
 - logistics processes 275
 - Object Naming Service (ONS) 275
 - Ratified EOCglobal Standards 277
 - SGTIN (serialized global trade item number) 278–9
 - specifications 276–9
 - standards 276–9
 - transponder classes 280
- equivalent circuit, Schottky diode 130
- equivalent radiated power (ERP) 118
- ERC recommendation 70–03 166
- estimated growth of RFID global market 2
- etching 19
- etching technique 355–6
- Eurobalise 166, 388–90
- European Article Numbering Association (EAN) 3, 273
- European Licensing Regulations 165–72
 - CEPT/ERC REC 70–03 166–70
 - European Telecommunication Standards 165
 - National Licensing Regulations in Europe 172–5
 - specific standards 171–2
 - standardized measuring procedures 170–2
- European Radio Office 166
- European Radio communications Office (ERO) 166, 172
- European Train Control System (ETCS) 388
- exchange system 370
- ExxonMobil Speedpass* 375

- Fahrsmart 367
- false alarm rate, ascertaining 268–9
- far field 112, 162
- Faraday's Law 70–2
 - metal surface 71
 - mutual inductance 71
 - open conductor loop 71
 - self-inductance 71
 - vacuum 70
- far-field in conductor loops 112
- FCC Part 15 175
- FCC regulation 175
- FDX 11, 39
- FDX-B transponder 237
- features of RFID 11–28, *See also*
 - Differentiation features of RFID
- ferrites 106–8
- ferromagnetic metals 38
- ferromagnetic random access memory (FRAMs) 12
- field
 - electric 50
 - magnetic 61
- field generator coil 264
- field strength 112–14
 - magnetic 61
 - maximum 65
 - path of 63
- fingerprinting procedures (Dactyloscopy) 4
- fitting transponders in metal 108–10
- flip chip technology 356
- flip-flops 231
- floating gate 308
- FRAM 309–10
- frame 254
- frame antenna 31
- frame size device integer (FSDI) 255
- free space attenuation 112
- free space path loss 46
- frequency band 166
- frequency divider 34–5
- frequency domain multiple access (FDMA) 194, 197
- frequency feature of RFID 21–2
- frequency modulation 181
- frequency ranges 156–64
 - 13.56 MHz (ISM, SRD) frequency range 159
 - 2.45 GHz (ISM, SRD) frequency range 161
 - 24.125 GHz frequency range 161
 - 27.125 MHz (ISM) frequency range 159–60
 - 5.8 GHz (ISM, SRD) frequency range 161
 - 6.78 MHz (ISM) frequency range 158–9
 - 9–135 kHz frequency range 157–8
 - inductively coupled RFID systems, frequency selection for 162–4
 - International Telecommunication Union (ITU) 164–5
 - ISM frequencies 156
 - selection 162–4
 - short-range devices (SRD), use of 156
 - UHF frequency range 160–1
- frequency shift keying (FSK) 185
 - 2 frequency shift keying (2 FSK) 55, 185
- full-duplex procedure (FDX) 11, 39, 235–6
 - FDX/HDX and SEQ systems, comparison between 53–4
 - representation of 40
- function cluster 295
- functional testing 263
- generator coil 31
- generator polynomial 191
- Germany, licensing regulations 172–5
- glass housing 13–15
- glass transponders 108, 348–51
- glaucoma 417
- global ID magazine 421
- global individual asset identifier (GIAI) 279
- graphite coating 50
- ground antenna 405
- group antenna 127
- GTAG (global tag) initiative 273–4
- half-duplex procedure (HDX) 11, 39, 53–4
- half-wave dipole ($\lambda/2$ dipole) 122
- hard magnetic metal 38
- hard tag 29, 34
- harmonic frequency 39
- harmonic 33
- HF interface 288, 302
- H-field 171
- hierarchical key concept 292–3
- high-end system 25
- high-end transponder 283
- host control interface (HCI) 344
- human medicine 417
- hybrid card 370
- hysteresis curve 35, 106

- I block 257
- ICARE 368
- ID-1 format 18–19
- Ident 421
- identification codes for animals 234
- identification of animals using RFID systems,
 - See Animal identification, standardisation
- identification system 391
- IDLE mode 247
- ignition lock 399
- IIC bus 299
- immobilisation system 325
- impedance matching 130, 137
- impedance sensors 153–4
- induced voltage 71
- inductance 66–8, 71
- inductance law 71
- inductive coupling 22, 40–5, 52–5, 218–19, 241
 - FDX/HDX and SEQ systems, comparison between 53–4
 - power supply to passive transponders 40–5, *See also under* Passive transponders
 - transponder to reader, data transmission 54–5
 - transponder, power supply to 52–3
- inductive modulation 242
- inductive radio system 22, 168–70
 - Germany, licensing regulations 173
- inductively coupled RFID systems 319–20
 - frequency selection for 162–4
- industrial associations 419–21
 - AIM 419–20
- industrial automation 25, 409–17
 - centralised control 411–12
 - decentralised control 412–13
 - inductively coupled transponders 409
 - industrial production 410–17
 - tool identification 409–10
- information processing in transponders 24–5
- information source 179
- injectible transponder 392
- injection needles 393
- inlet foil 352
- input capacitor 129
- input impedance 118–19, 139
- integrated reader ICs 324–31, *See also* Single-chip reader IC
 - driver 325
 - load modulation procedure 326
 - on-chip oscillator 325
 - received signal conditioning 325
 - U2270B 327
- interdigital transducer 55, 145
- interference reflection 148
- international container transport 390–1
- International Telecommunication Union (ITU) 164–5
- internet links 422–3
- interrogation field strength (H_{\min}) 77–83, 139, 243
 - energy range of transponder systems 80–2
 - interrogation zone of readers 82–3
- interrogation pulse 147
- interrogation zone 82–3, 127
- interrogator-driven procedures 198
- ISM frequency ranges 155
- ISO/IEC 10374 390–1
- ISO/IEC 10536 49, 240
- ISO/IEC 11784, identification code 233–4
- ISO/IEC 14443 transponder, RF interface for 286
- ISO/IEC 6346 267
- ISO/IEC 69871 267
- ISO/IEC 69872 267
- ISO/IEC 69873 267
- ISO/IEC 9798–2 227
- ISO/IEC container 267
- ISO/IEC 18000 Series 270–2, *See also under* Item management, standardisation
- isotropic emitter 112, 117
- item management, standardisation 270–82
 - EPCglobal Network 274–82, *See also individual entry*
 - GTAG (global tag) initiative 273–4
 - GTAG transport layer (physical layer) 273–4
 - ISO/IEC 18000 Series 270–2
- jamming, RF interface 217–18
- junction capacitance, passive microwave transponders 130
- junction resistor, passive microwave transponders 130
- key 292
 - application specific 294
 - application's own 294

- key (*continued*)
 hierarchical 293
 master 228
 secret 292
 keyring transponder 17
- label 19–20
 lamination, in contactless smart cards
 manufacturing 359
 langasite 315
 lead frame 356
 Lenz's law 85
 licensing regulations 155–78
 line codes 179
 linear detection, passive microwave
 transponders 131
 lines of magnetic flux 62
 lithium niobate 55, 144
 lithium tantalate 55, 144
 load modulation 43, 52, 94–100
 capacitive load modulation 97–8
 demodulation in reader 98
 integrated reader ICs 326
 modulation resistor 96
 ohmic load modulation 95–7
 with subcarrier 43–4, 285–6
 Q factor influence 98–100
 load resistance (R_L) 92–3, 187
 load resistor 43, 129
 logistics processes, EPCglobal Network 275
 longitudinal redundancy check (LRC)
 procedure 190–1
 long-range system 22, 45
 longwave 157
 loop antenna 171
 low-barrier Schottky diode 47
 low-cost transponder 163
 low-end system 24
 Lufthansa 361
- machine-readable zone (MRZ) 382–3
 magnetic alternating field 63
 magnetic coupling 22, 49
 magnetic field 61–110, *See also* Interrogation
 field strength (H_{\min}); Resonance; Total
 transponder–reader system;
 Transformed transponder impedance
 (Z_T)
 abbreviations used conductor loops, 62–5
 constants used 62
 coupling coefficient (k) 68–70
 Faraday's Law 70–2
 inductance (L) 66–7
 magnetic field strength (H) 61–6
 magnetic flux 66
 magnetic flux density 66
 mutual inductance (M) 67–8
 optimal antenna diameter 65–6
 system parameters, measurement 100–6
 transponder, practical operation of 76–7
 units used 62
 magnetic flux 66
 magnetic materials 106–10, *See also* Ferrites
 fitting transponders in metal 108–10
 properties 106–7
 magnetisation characteristic 106
 magnetostriction 38
 main radiation direction 117
 Manchester code 181, 205
 manipulation 227
 market for smart cards 4–6
 mass production 410
 master key 228
 master-slave principle 317–18
 mat 405
 matching 136
 circuit 334
 current 54
 power 53
 voltage 54
 material flow 411
 measurement
 acceleration 312, 315
 compression 315
 distance 313
 flow 312
 gases 312
 light 312
 moisture 312
 pH value 312
 physical quantities 322
 speed 313
 temperature 315
 medical applications 417–18
 artificial intraocular lens 418
 glaucoma 417
 human medicine 417
 microcoil 418
 memory architecture, transponder 289–300
 read-only transponder 289–91
 segmented memory 294–5

- transponder with cryptological function
 - 291–3
- writable transponder 291
- memory block 238
- memory capacity 28
- memory cards 5
- memory technology 307–11
 - EEPROM 308–9
 - FRAM–EEPROM, performance
 - comparison 310–11
 - FRAM 309–10
 - RAM 307–8
 - (S)RAM memory 307
- metal
 - amorphous 35, 38
 - foil 50
 - hard magnetic 38
 - lid 108
 - surface 15, 71, 108, 115–16, 403, 409
- metallic surface 107
- microchip 9, 72, 347
 - operating voltage 77
 - power consumption 92
 - power supply 72
- microcoil 418
- microprocessor 6, 300–7
 - operating system 300
 - smart card 4–5, 300
- microprocessors, architecture 300–7
 - command processing sequence 302
 - dual interface card 303–7, *See also individual entry*
- microstrip antenna 125–7
- microwave frequency 45
- microwave range 22
- microwave system 320–1
- microwave transponders 127–44
 - active transponders, power supply of 137
 - cancellation 137–8
 - equivalent circuits of transponder 127–9
 - modulated backscatter 139–41
 - passive microwave transponders, power supply of 129–37, *See also individual entry*
 - practical operation of 127–44
 - read range 141–4
 - reflection 137–8
 - SAW transponders 322–3
 - sensitivity of transponder 138–9
- microwaves 33–4
- MIFARE® application directory 295–7
- Miller code 181, 247
- mobile telephone 303
- modem 179
- modified Miller code 181
- modulated backscatter 48, 139–41
- modulated radar cross-section 115
- modulated reflection cross-section,
 - electromagnetic backscatter coupling 47–8
- modulation 54, 142, 179–88, 319–20, *See also Digital modulation procedures*
- modulation capacitor 97
- modulation index 142
- modulation product 182
- modulation resistor 96, 286
- modulator 179
- motor electronics 400
- MP&PR specification 274
- multi-access procedures 194–211, *See also Anticollision*
- ‘Multi-shot’ device 393
- multilevel modulation 187
- multiplexer 383
- mutual authentication 227
- mutual authorisation 292
- mutual inductance 67–8, 71, 85
- mutual symmetrical authentication 227–8
- National legislative regulations 172
- National Licensing Regulations in Europe 172–5, *See also under European Licensing Regulations*
- near field 43, 112
- near-field communication (NFC) 57–9, 339–46
 - active mode 57–9
 - application software 341
 - applications 375–80
 - communication protocol 341
 - data transceiver 340
 - load modulator 341
 - middleware 341
 - NFC wired interface 345–6
 - passive mode 58
 - secure NFC 341–6
- near-field in conductor loops 112
- noise 142
- non-linear resistance 33
- NRZ code 181, 205, 245

- occipital bone 394
- OCR reader 3
- OCR system 3
- OEM reader 338
- offered load 199
- offline systems, access control 385–7
- ohmic load modulation 95–7
- on-chip oscillator 325
- on-chip trimming capacitor 52
- one-port resonator 151
- one-time-pad 230
- online systems, access control 385
- on-off keying 245
- open conductor loop 71
- operating frequency 13, 26, 84
- operating principles 29–59, *See also* 1-Bit transponders; Close-coupling; Electrical coupling; Electromagnetic backscatter coupling; Full-duplex procedure (FDX); Half-duplex procedure (HDX); Sequential procedures (SEQ); Surface acoustic wave (SAW) transponders
- operating voltage 77
- optimal antenna diameter, RFID magnetic field 65–6
- order processing 417
- oscillator 142, 319, 325
- OSI layer model 256
- overlay foil 352

- parallel regulator 77
- parallel resonant circuit 72, 74
- parity bit 189
- parity checking 189–90
- passive microwave transponders, power supply of 129–37
 - impedance matching 130
 - junction capacitance 130
 - junction resistor 130
 - linear detection 131
 - peak value rectification 131
 - radiation resistance 132
 - Schottky detector 130–6
 - voltage doublers 132
- passive mode, NFC 58–9
- passive transponders 13, 22–4, 40–5, 76
- password 292
- patch antenna 125–7
- payment 303
- PCD 243, 259

- peak value rectification, passive microwave transponders 131
- penetration depth 163
- permanent magnet 36
- permeability 106
- phase 102
 - modulation 98, 181
 - noise 142
 - phase shift keying (PSK) 185–6, 242
 - position 315
- physical principles of RFID 61–154, *See also* Antennas; Electromagnetic waves; Magnetic field; Microwave transponders; Surface waves
- Piezo effect 55, 144
- Piezoelectric crystal 144
- pigeon ring 396
- planar antenna 125
- plastic housing 13–15
- plastic package (PP) 13
- plastic transponders, manufacture of 351
- polarisation direction 139
- polarisation loss 114
- polarisation of electromagnetic waves 114–16
- polling procedure 198
- polyethylene foil 30
- polymer thick film pastes (PTF) 354
- power consumption 92
- power-down mode 305
- power level 166
- power management unit 304
- power matching 53
- power on logic 286
- power saving mode 305
- power supply 13, 99, 129, 241–2, 283
- Poynting radiation vector S 113
- production process 410
- programming station 386
- protection by cryptographic measures 226–32
 - against attempted attacks 226
 - authentication using derived keys 228
 - encrypted data transfer 228–32
 - mutual symmetrical authentication 227–8
- protection of privacy 215
- protocol 256–8
- protocol control byte (PCB) 257
- proximity cards (PICC) 243
- proximity-coupling smart cards–ISO/IEC 14443 22, 243–58, 263, 362
 - applications 362
 - communication interface 245–7

- initialisation and anticollision (Part 3)
 - 247–54
- physical characteristics (Part 1) 243
- radio frequency interference (Part 2) 243–7
- transmission protocols (Part 4) 254–8
- pseudorandom sequence 231
- public transport 362–72
 - automatic fare collection (AFC) 362
 - benefits of RFID systems 363–5
 - CALYPSO, EU Project 368–72
 - dual interface card 370
 - Fahrsmart* project 367–8
 - fare systems using electronic payment 365
 - Germany–Lüneburg, Oldenburg 367–8
 - hybrid card 370
 - ICARE, EU Project 368–72
 - Korea–Seoul project 366–7
 - market potential 366
 - open financial exchange systems 370
 - requirements 363
 - starting point 362–3
- pulse-pause coding 181
- pulse position modulation (PPM) procedure 259
- pulse radar 323
- pulsed system 39

- Q factor 75
 - influence 98–100
 - measuring 102–6
- Quartz 144
- quick-release taper shaft 267

- R block 257
- R&TTE Directive 170, 429
- R&TTE homepage 172
- radar cross-section (RCS) 115–16
- RADAR technology 47, 115
- radiation density (S) 112, 115
- radiation pattern 117
- radiation resistance 118, 122, 125, 132
- Radio Equipment and Systems (RES) 171
- radio frequency (RF) procedure 29–33
- radio licensing regulations 156–78
- radio service 155
- radio system 155
- rail traffic 166
- random number 227, 398
- range feature of RFID 21–2, 26–7
- Rayleigh wave 144

- read range of microwave transponders 141–4
- readers 6, 8, 317–46, *See also* Integrated reader ICs; Near-field communication (NFC)
 - components 317–24
 - control unit 323–4
 - data flow in an application 317
 - designs 338–9
 - inductive systems, connection of antennas for 331–8
 - master–slave principle 317–18
 - RF interface 318–23
- read-only transponders 24, 289–91
- REC 70–03 166
- received power 143
- received signal conditioning 325
- received signal 179
- receiver arm 319
- receiver sensitivity 175
- receiver 179
- reference card 264, 266
- reflection characteristics 48
- reflection cross-section 47
- reflection in microwave transponders 137–8
- reflection of electromagnetic waves 115–16
- reflective delay lines 148, 150–1
- reflective properties 115
- reflectors 55–7, 124, 147
- regulations 166, 423
- relay attacks 224–6
- release taper shaft 267
- remote coupling system 22
- REQB (REQUEST-B) command 251
- REQUEST command 198, 203
- resistance, nonlinear 33
- resonance 72–6
 - equivalent circuit 35, 73
 - parallel resonant circuit 74
 - Q factor 75
- resonant frequency 72, 86, 102
- resonant sensors 151–3
- response pulse, phase position 315
- retention bolts 409
- retention knob 267
- RF innovations 398
- RF interface 283–6
 - for ISO 14443 transponder 286–7
 - load modulation with subcarrier 285–6
 - readers 318–23, *See also under* Readers
- RF interface, attacks on 216–26
- communication interception 217

- RF interface, attacks on (*continued*)
 extending the read range 218–26, *See also*
 Relay attacks
 jamming 217–18
- RF procedure 29
- road toll systems 167
- road transport and traffic telematics (RTTT)
 167–8
- robots 338
- S block 257
- saw on foil 348
- scanning pulse 55
- scatter aperture, antennas 119–22
- Schottky detector 130–6
- Schottky diode 47, 130
- screen printing 19
- screen printing technique 353–5
- scutulum 394
- security authentication module (SAM) 228
- security element 29
- security logic 286–300
- security of RFID systems 213–32, *See also*
 Attacks on RFID systems; Protection by
 cryptographic measures
 ‘RFID Right to Know Act of 2004 (SB
 0867)’ 214
- security requirements 27–8
 smart card 304
- security system 226
- security tag 34
- segmented memory 294–5
 fixed segmentation 295
 free segmentation 295
- segmented transponder 294
- SELECT command 203
- selection criteria for RFID 25–8, 414
 according to functionality 25
 EEPROM 414
 memory capacity 28
 operating frequency 26
 range 26–7
 security requirements 27–8
 SRAM 414
 technical parameters 25
- self-inductance 71
- semiconductor circuit 34
- semi-passive transponders 22
- semitransparent contactless smart card 18
- sensitivity of microwave transponders 138–9
- sensor coil 31
- sensor data 311
- sensor effect 149–54
 impedance sensors 153–4
 reflective delay lines 150–1
 resonant sensors 151–3
 switched sensors 154
 temperature sensor 151–2
- Seoul 366–7
- sequential ciphering 230–2
- sequential procedures (SEQ) 11, 52–7, *See*
also Inductive coupling
- sequential systems (SEQ) 11, 52
- sequential transponder 11
- serial number 24, 202, 206, 222, 278, 289,
 307, 347, 381, 399
- serialized global trade item number (SGTIN)
 278–9
- series resonant circuit 84
- shift register 192
- shortening factor 123
- short-range devices (SRD) 23, 156, 166, 170,
 424
- shortwave frequency 217
- shunt regulators 77
- shunt resistor 77
- sidebands 142, 182
- sigma modulation 139
- signal coding 179
- signal decoding 179
- signal processing 179
- signal representation 179
- signal travelling times 312
- silver conductive paste 50
- single-chip reader IC 327–31
- ‘Single-shot’ devices 393
- single wire protocol, NFC 343–5
- ski lift 383
- ski Tickets 383–4
- slot 204
- slot antennas 127
- slotted ALOHA (S-ALOHA) procedure
 201–11, 251
 binary search algorithm 204–9
 capture effect 202
 command set for anticollision 203
 dynamic binary search procedure 209–11
 dynamic S-ALOHA procedure 203–4
 REQUEST command 203
 SELECT command 203
- smart cards 4–6, *See also* Memory cards

- advantages 4
- disadvantages 5
- dual interface smart cards 25
- load modulation, measuring 264–6
- test methods for, ISO/IEC 10373 263–7
- test procedure for 266–7
- smart label transponders 19–20
- software application 317
- sonotrode 353
- space division multiple access (SDMA) 196–7
- speed of light 110
- spherical emitter 112
- split-phase encoding 181
- sporting events 405–8
- spread spectrum 194, 274
- spurious emissions 170
- spying out 215
- square law detection 132
- standardisation 233–82, *See also* Animal identification; Anti-theft systems for goods, standardisation (VDI 4470); Item management, standardisation
- standardised measuring procedures, in European licensing regulations 170–2
- standards and Regulations 423–9
- state diagram 289
- state machine 12, 24, 283, 289
- static random access memory (SRAM) 12, 414
- sticky labels 20
- stock keeping, animal identification 391–5
 - bolus 394
 - collar transponders 392
 - ear tags 392
 - injectible transponders 392
 - injection needles 393
 - ‘multi-shot’ device 393
 - scutulum 394
 - ‘single-shot’ devices 393
- stream ciphering, *See* Sequential ciphering
- stretching measurement 315
- subcarrier frequency 187, 242, 245
- subcarrier 43, 187–8, 245
- subharmonic procedure 45
- subharmonic 35, 39
- superposition 138
- surface resistance 354
- surface acoustic wave (SAW) transponders, microwave system for 22, 55–7, 144, 322–3
- surface waves 144–54, *See also* Sensor effect creation of 144–6
 - reflection 146–7
 - SAW transponders, functional diagram 147–9
- swept signal 31
- switched sensors 154
- symmetrical key procedure 229–30
- synchronisation 235
- system clock 288
- T/R 22–04 171
- T/R 60–01 171
- tag 29
- taper shaft 409
- technical journals 421–2
- telemetry transmitter 170, 311
- temperature measurement 312
- temperature sensor 151–2, 311
- test mode 347
- Thomson equation 73
- three pass mutual authentication 227
- ticketing 25
- time domain multiple access (TDMA) 194, 197–9
- tool holder 409
- tool identification 409–10
- total transponder–reader system 84–100, *See also* Load modulation; Transformed transponder impedance (Z_T^+)
- Touch & go 48
- traffic telematics 167–8
- transaction time 303
- transformed impedance 43
- transformed transponder impedance (Z_T^+) 85–94
 - coupling coefficient (k) 89–92
 - influencing variables of 88
 - load resistance (R_L) 92–3
 - transponder capacitance (C_2) 91
 - transponder inductance (L_2) 93–4
- transformer coupling 112
- transformer-type coupling 43
- transmission channel 179
- transmission error 179
- transmission frequency 13, 88
- transmission medium 179
- transmission protocol, ISO 14223 238
- transmitter arm 319
- transmitter output power 337
- transmitter 179
- transponder(s) 6, 8–9, 198, *See also* Active transponders; Passive transponders

- transponder(s) (*continued*)
 - access control 387–8
 - attacks on 215–16
 - classes, EPCglobal Network 280
 - construction formats 13–21
 - with cryptological function, memory architecture 291–3
 - electromagnetic backscatter coupling
 - information processing in 24–5
 - manufacture of 347–59
 - with memory function 283–300, *See also*
 - Address and security logic; Dual port EEPROM; Memory architecture, transponder; MIFARE®
 - application directory; RF interface
 - power supply to
 - read-only transponders 24
 - resonant frequency, measuring 102–6
 - transponder inductance (L_2) 93–4
- transport container 273
- transport layer 273
- transport systems 388–91
 - Eurobalise S21 388–90
 - international container transport 390–1
- trimming capacitor, on-chip 52

- U2270B 325
- UHF frequency range 160–1
- UHF frequency range 160–1, 273
- UHF range 22
- unipolar code 179
- unipolar RZ code 181
- unique number 24, 307
- Universal Code Council (UCC) 273
- Universal Product Code (UPC) code 3

- vehicle identification 166
- vehicle theft 398
- vernem cipher 230
- VHF range 160
- vicinity-coupling smart cards 22, 258–63
- voice identification 4, 6
- voltage divider, capacitive 50
- voltage doubler 132
- voltage matching 54

- wafer 347
- waste disposal 404–5
- wavelength 111
- winding technique 352
- wire-bound carrier systems 157
- wired interface, NFC 345–6
- writable transponder, memory architecture 291
- write time 310

- Yagi–Uda antenna 124, 220–1